



LINDE L – 14 AP 2005

Electric Pedestrian Pallet Stacker





The above Info is to the best of our Knowledge, but it's not binding in detail.





TECHNICAL DATA

DESCRIPTION	L – 14 AP PEDESTRIAN PALLET STACKER
Load Capacity	1400 KG
Load Centre	600 MM
Axle Centre to Load Face	727 MM
Wheel base	1303 MM
Height of Mast, Lowered	1990 MM
Height Of Mast, extended	3460 MM
Free lift	150 MM
Lift	2924 MM
Ground Clearence, Centre of Wheelbase	30 MM
Travel Speed with Load	7 Km/h
Travel Speed Without Load	9 Km/h
Lifting Speed with Load	0.16 m/s
Lifting Speed without Load	0.25 m/s
Lower Sped With / without Load	0.45 m/s
Drive Motor, 60 Min Rating	1.5 kW
Lift Motor, @ 15 % Rating	3 kW
Battery Voltage/Rated Capacity	24 V / 240 Ah
Battery Weight	240 Kg
Type of Drive Control	Electronic (LDC)
Fork Carriage width	780 MM
Fork Spread Max / Min	560 / 680 MM
Fork Dimension (L X W)	1150 / 180 MM
Fork Thickness	71 MM
Length of Fork Face	882 MM
Noise Level at Operator's ear	<65 dB(A)

The above Info is to the best of our Knowledge, but it's not binding in detail.





MACHINE PHOTOS





The above Info is to the best of our Knowledge, but it's not binding in detail.

S.F no. 133/3, Opp – Hindustan Petroleum DepotIrugur VillageA.G Pudur PostCoimbatore – 641103.Website: www.europeaengineering.comMobile No:+91 93606 56789+91 96774 36789.









The above Info is to the best of our Knowledge, but it's not binding in detail.